



Distribuidora Térmica Acústica del Centro, S. A DE C. V.

Norte 80 No. 4313 Col. Malinche

07899 México D, F. Tel (s): 01 55 2603-5234, 5551-5038 Radio Nextel: 92*900430*2

01 55 2603-0450, 4981-0651 Correo: aislamientos_dta@prodiqy.net.mx

Web site: www.dtamexico.com

CINCHOS DE NYLON DURO DYNE DYN-O-TIES

Whenever your job calls for securing round flexible duct to outlets, pipes or fittings, you can do the job better, faster, and at low cost using **DYN-O-TIES™**, flexible duct ties.

No tapes, no screws, no clamps. Position the flexible duct and slip a **DYN-O-TIE** around the flexible duct over the joint. Draw tight with our ratchet action hand tool. A twist of the wrist completes the job by clipping off the excess nylon tab for the neatness and most secure connection you could want.

DYN-O-TIES, when properly installed, provide secure, self-extinguishing joints when connecting certain types of flexible duct listed by Underwriters Laboratories Inc., class 1.

* **Test Method:** Ties is secured at both ends forming a loop. A weight is suspended from the bottom of loop to determine tensile strength of **DYN-O-TIE** strap.



Nylon 66V2. Self-extinguishing. Fungus inert. Normal service temperature range: -40°F to 185°F.

Test Results: Nylon – 275 lbs. *

ITEM NUMBER	CODE	LENGTH	MAXIMUM DIAMETER	DESCRIPTION	QTY/PKG
8251	DN-24	24	7"	NYLON DYNOTIES	25
8311	DN-36	36	11"	Self extinguishing, mildew resistant, high tensile nylon with tab release.	25
8305	DN-48	48	15"	Service temperature -40°C to 85°C	25

DYN-O-TIE INSTALLATION TOOL

This light weight tool is commonly used to install most makes of nylon duct ties.

ITEM NUMBER	CODE	DESCRIPTION
8229	DIT-2	Dyn-O-Ties Installation Tool for use with nylon Dyn-O-Ties.