## SAFETY DATA SHEET

SECTION 1 - IDENTIFICATION		
Manufacturer's name and addre	ss: Supplier's name and address:	
K-FLEX US	Refer to Manufacturer	
K-FLEX USA 100 K Flex Way Youngsville, NC 27596 USA		
Telephone No. Website Address Product Identifier Chemical Name Recommended Use	<ul> <li>: (800) 765-6475</li> <li>: <u>www.kflexusa.com</u></li> <li>: K-FLEX Clad IN Jacketing</li> <li>: Clad IN Jacketing</li> <li>: Clad IN Jacketing</li> <li>: This product is classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200C.</li> </ul>	
SECT	ION 2 – HAZARD(S) IDENTIFICATION	
Hazardous Ingredient Hazardous Gases	<ul> <li>The dangerous ingredients (see sec. 3) are in the compound in lower concentrations with reference to what established by the article 3, par. 6, of D.M. 28/1/92</li> <li>Combustion or thermal decomposition will involve toxic and corrosive vapors: carbon monoxide (CO), hydrochloric acid, carbon dioxide, and other organic compounds.</li> </ul>	

ngredients : Substances considered dangerous for the health in accordance with Directive 67/548/CEE and successive modifications, or for which limits of exposition are recognize Dangerous ingredients, but in lower concentrations on account of law limits:		548/CEE and successive nits of exposition are recognized.
	2,2' – Benzothiazyl disulfide	Antimony trioxide
N.CAS	120-78-5	1309-64-4
%	<0.5	<7
DANGER SYMBOLS	Xi,n	Xn
DANGER SENTENCES	R 43-53	R 40
CAUTION ADVICE	S24-36/37-60	S22 S36/37



## **SECTION 4 – FIRST-AID MEASURES**

Inhalation	: Remove patient from exposure, keep warm and at rest. Use suitable respiratory protection measures. If breathing is irregular or has stopped, proceed with artificial respiration. Obtain medical attention.
Skin Contact	: When product is hot: Cool affected areas with cold water. Cover a clean cloth or sterile gauze and call immediately for medical help. Do not try to remove product from skin or remove soiled clothing, as this may cause injured skin tissue to be torn off.
	: This product is an inert solid. In case particles come into the eye, remove by irrigating with eye wash solution or clean water, holding the eyelids apart. Obtain medical attention.
Ingestion	: Unlikely route of exposure. First aid normally not necessary.

SECTION 5 – FIRE-FIGHTING MEASURES	
Extinguishing Media	: Water, CO <sub>2</sub> , froth, chemical powders on the ground of the materials involved in the burning.
Special Firefighting Procedures	: In the presence of combustion or carbonization gases, any fire-fighting, rescue, and clearing up activities should be undertaken only with heavy-duty respiratory and eye protection equipment.
Decomposition Products	: Combustion or thermal decomposition will involve toxic and corrosive vapors: carbon monoxide (CO), hydrocarbons, carbon dioxide, smoke, hydrochloric acid.

# **SECTION 6 – ACCIDENTAL RELEASE MEASURES**

Personal Precautions	: You have to adapt necessary measures to reduce contact with skin as much as possible. Wear gloves or use other protective means. Avoid contact with development of vapors in case of hot working. Assure good ventilation of workplaces and equipment where the product can be brought to high temperatures.
Emergency Procedures	: None.

SECTION 7 – HANDLING AND STORAGE	
Hints for Safe Handling Hints for Fire and Explosion Protection Hints for Warming	<ul> <li>See sec. 6</li> <li>Avoid breathing fumes. Use respiratory protection.</li> <li>(e.g. when welding) Sufficient ventilation should be provided.</li> </ul>

100 Nomaco Drive Youngsville, NC 27596



800-765-6475 Fax: 800-765-6471

www.kflexusa.com

Storage Recommendations

: Keep in adequately ventilated rooms, protected from inclement weather and at such a temperature to keep the proper technological properties.

#### SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Medical Conditions Aggravated by Exposure Codes Used General Health Measures **Engineering Controls** 

: Not established.

: N/A

: N/A : Local exhaust ventilation is recommended for control of airborne dust, fumes, and vapors in confined areas.

#### SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Rolls with or without PSA or pre-adhered to elastomeric pipe and sheet insulation in various sizes with.
Color	: Gray.
Odor	: Negligible to no odor.
Melting Point	: N/A
Boiling Point	: N/A
Lower Explosion Limit	: N/A
Upper Explosion Limit	: N/A
Vapor Density (Air = 1)	: N/A
Solubility	: Insoluble
Specific Gravity (H <sub>2</sub> O = 1)	: N/A
Flash Point	: N/A

SECTION 10 – STABILITY AND REACTIVITY	
Chemical Stability	: Stable up to 200° c (392° F)
Incompatibility	: N/A
Decomposition Products	: Temperatures above 300° C (572° F) lead to the decomposition of the polymers. Thermal decomposition products are toxic and corrosive: hydrocarbons, carbon dioxide, carbon monoxide, smoke, hydrochloric acid.
Hazardous Reactions	<ul> <li>Plants under controlled conditions. Work according to local and national force directives.</li> </ul>

### **SECTION 11 – TOXICOLOGICAL INFORMATION**

Effects on short- and long-term Exposure

: When used and handled according to specification, the

100 Nomaco Drive Youngsville, NC 27596



800-765-6475 Fax: 800-765-6471

www.kflexusa.com

product does not have any harmful effect to the best of our knowledge.

#### **SECTION 12 – ECOLOGICAL INFORMATION**

Classified as non-hazardous to waters.

#### SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal

: Not a hazardous waste. Dispose of in accordance with local, state, and federal regulations.

#### **SECTION 14 – TRANSPORT INFORMATION**

Non-hazardous material.

## **SECTION 15 – REGULATORY INFORMATION**

N/A

## SECTION 16 – OTHER INFORMATION

Revised January, 2018. The information and recommendations contained herein are based upon data that is accurate and reliable, to the best of K-FLEX USA, LLC knowledge and belief. With respect to information and recommendations, K-FLEX USA, LLC makes no representations or warranties of any kind or nature, expressed or implied.

100 Nomaco Drive Youngsville, NC 27596



800-765-6475 Fax: 800-765-6471