

CT-DT 3520

DUCT TAPE

FEATURES:

- ◆ Aggressive synthetic rubber adhesive
- ◆ Flexible and durable
- ◆ Conform well to irregular surfaces
- ◆ Perform well in warm and cold conditions

TYPICAL APPLICATION:

- ◆ Sealing joints, repair and masking, interior and exterior



Construction		<ul style="list-style-type: none"> ◆ LDPE coated woven polyester/cotton mesh ◆ Synthetic rubber adhesive 	
PROPERTIES		Metric	English
Backing (mesh)		35 +/-1 mesh (19x16 counts/inch)	35 +/-1 mesh (19x16 counts/inch)
Total Thickness		0.16 mm	6.3 mil
Peel Adhesion to Steel		18.1 N/25mm 0.74 Kg/cm	65 Oz/inch
Rolling Tack (11 mm ball)		12 cm	4.72 inch
Tensile strength		3000 N/m	16.8 Lb/inch
Holding power		> 3 hours	> 3 hours
Service Temperature		-15 ~ +60° C	5 ~ + 140° F
Core I.D.		76mm	3"
Color		Silver grey, other colors available by request	
Roll width		50mm (2"), 60mm, 75mm (3"), 100mm (4")	
Roll length		27m (30 yards), 30m (100'), 45m (50 yards), 50m, 100m	

1. The data above are typical results from tests conducted on samples taken from production runs and may be updated without notice. Typical values are not intended to be used for specification development.
2. The product should be stored in the original packaging material at 20 +/- 5°C and 40-60% relative humidity and protected from direct sunlight, heat and moisture. Shelf life: One year when stored at the conditions described above.
3. The surface to which the tape is applied must be clean, dry, free of grease and oil and other contaminants and deposits. Recommended temperature of application: 50 – 105 °F (10 – 40 °C).
4. The user is responsible for determining whether the product is fit for a particular surface and suitable for user's application. The user should make necessary tests and trial-application of the tape to confirm suitability for user's special purpose and method of application.
5. Self adhesive tapes are designed for sealing applications only. In the instance when the sides of the joint are subject to mechanical stress, both sides should be securely positioned using appropriate fasteners or hangers prior to the self adhesive tapes application.
6. Calem Technology warranty that the product is free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment, Calem Technology shall, upon notification thereof and substantiation that the product have been stored and applied in accordance with the above requirements, at Calem Technology discretion, replace or credit the product's purchasing price equivalent.
7. Limitation of liability. Calem Technology Inc. and seller of CT Tape products will not be liable for any loss or damage arising from the CT Tape product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



CT TAPE

1-604-277-6643
186-8120 No. 2 Road
Richmond, BC
V7E 3E6, Canada